

YC835 Digital discussion system



YC835M Main Controller

- Number control of the main unit and conference system single connecting and sounds signal adapted the same cable. (8DIN)
- Operate independently or connect with computer external and use with software simultaneously, managing kinds of conference function (conference mode or operation: Appointed to speak, Free, Applied to speak and FIFO, etc)
- Single unit can manage functions: Open, Limit, FIFO
- Has three conference management: (Open) (FIFO) (LIMIT)
- Can setting speaking number 1~9 or Open.
- Built-in video camera tracking function.
- The board has LCD screen display, 122x32 lattice demonstration conference pattern. Also, it has function button, knob for system setting and adjusting.
- Has audio signal output interface, external connect with REC or audio equipments
- Frequency response : 100HZ ~18KHZ; Total harmonic distortion: 100HZ~18KHZ
System sound output < 0.1%
- Consumption : 115W
- Adapted AC220V power
- In accordance with international conference equipments and international safety standard UL, CE certificate.
- N. G : 11.8kg
- External dimensions : 485mm (including microphone hand) x100mm (2U, including foot pad) x355mm (WxHxD. It can be put on the table or install in the 19inch frame
- This system can be used with video camera automatic tracking system and voting system.



YC835C/D Chairman/Delegate Unit

Chairman unit

Including the functions of the delegate unit, chairman unit has other following functions.

- The chairman unit number in the system is unrestricted, can join in any position of the system.
- Turn down delegate MIC by press the priority button.
- Indicative sound for chairman unit (optional)

Delegate unit

- Designed in accordance to ISO and IEC914.
- The system power supply for all the delegate units is provided by the main frame at 12 safe voltages.
- 3.8P-DIN plugs for system T-type connection.
- Electric capacity type microphone, equipped with windshield cover.
- Extended pipe optional.
- The annular red indicator lamp could show the state of the microphone.
- The microphone has a speaking button and indicator lamp; it can control the state of speech.
- Auto-off function: The microphone would close automatically in 35 seconds after making a speech.